

PROCESS FLOW SHEET




FIG 1

BEST AVAILABLE COPY




BEST AVAILABLE COPY

MICROSTRUCTURES



1. BETATISED 750°C/3Min./CWQ



2. BETATISED 750°C/3Min./CWQ

FIG 2



BEST AVAILABLE COPY


MICROSTRUCTURES




1. REHEAT 200°C/10 Min./CWQ



2. REHEAT 300°C/10 Min./CWQ




3. REHEAT 400°C/10 Min./CWQ



4. REHEAT 500°C/10 Min./CWQ




5. REHEAT 600°C/10 Min./CWQ



6. REHEAT 700°C/10 Min./CWQ

FIG 3



7. REBETATISED 550°C/10Min./CWQ



8. REBETATISED 575°C/10 Min./CWQ



9. REBETATISED 600°C/10Min./CWQ



10. REBETATISED 625°C/10Min./CWQ



11. REBETATISED 650°C/10Min./CWQ



12. REBETATISED 675°C/10Min./CWQ



13. REBETATISED 700°C/10 Min./CWQ

BEST AVAILABLE COPY

FIG 4





FIG 5



SME: SHAPE MEMORY EFFECT
 CWQ: COLD (ORDINARY) WATER QUENCHED

FIG 6



BEST AVAILABLE COPY




FIG 7



BEST AVAILABLE COPY

BEST AVAILABLE COPY




FIG 8